



Protected by
PAK ARMORING (PVT) LTD.



PAK ARMORING



ARMORED VEHICLES SPECIALIST

One Team, One Goal, Saving Lives





PRIDE OF PAK ARMORING

**Pak Armoring have the privileged of
Armoring the vehicles of V.VIPs
at the highest level**



UQAAB (Multi Purpose Armored Vehicle)

Protected by
Pak Armoring (Pvt) Ltd.



Protection Level **B6**
also available on request.

Protection Level **B7**

Transparent Armor: B7 (7.62 x 51 API)

- Replace OEM glass with curved & flat ballistic glass.
- All ballistic glass is rated to B7 standards.

Armor: B7 Armour Materials (7.62 x 51 API)



UQAAB designed for Military Personnel and VIP Transport. Full Vehicle is protected with certified CEN B7 / NIJ IV Armor; Carry up to 8 soldiers with full equipment. Also equipped with several armored enhancements, such as a blast mitigation floor mat, provided with a roof turret, .30 or .50 CAL Machine Guns, seven springs loaded gun-ports are integrated at each seat. Heating, ventilation and air conditioning system, automatic fire engine suppression system and heavy duty 300 AMP alternator.



Ballistic Standards Chart



NIJ Standard - 0108.01 BALLISTIC RESISTANT PROTECTIVE MATERIALS

ARMORE TYPE	WEAPON	TEST AMMUNITION	NOMINAL BULLET MASS	SUGGESTED BARREL LENGTH	REQUIRED BULLET VELOCITY	REQUIRED HITS PER ARMOR SPECIMEN
I		22 LRHV	2.6 g	15 to 16.5 cm	320 ± 12 m/s	5
		Lead	40 gr	6 to 6.5 in	1050 ± 40 ft/s	5
		38 Special RN Lead	10.2 g 158 gr	15 to 16.5 cm 6 to 6.5 in	259 ± 15 m/s 850 ± 50 ft/s	5
II-A		357 Magnum	10.2 g	10 to 12 cm	381 ± 15 m/s	5
		JSP	158 gr	4 to 4.75 in	1250 ± 50 ft/s	5
		9 mm FMJ	8.0 g 124 gr	10 to 12 cm 4 to 4.75 in	332 ± 12 m/s 1090 ± 40 ft/s	5
II		357 Magnum	10.2 g	15 to 16.5 cm	425 ± 15 m/s	5
		JSP	158 gr	6 to 6.5 in	1395 ± 50 ft/s	5
		9 mm FMJ	8.0 g 124 gr	10 to 12 cm 4 to 4.5 in	358 ± 12 m/s 1175 ± 40 ft/s	5
III-A		44 Magnum	15.55 g	14 to 16 cm	426 ± 15 m/s	5
		Lead SWC	240 gr	5.5 to 6.25 in	1400 ± 50 ft/s	5
		Gas Checked 9 mm FMJ	8.0 g 124 gr	24 to 26 cm 9.5 to 10.25 in	426 ± 15 m/s 1400 ± 50 ft/s	5
III		7.62 mm 308 Winchester FMJ	9.7 g 150 gr	56 cm 22 in	838 ± 15 m/s	5
IV		30-06 AP	10.8 g 166 gr	56 cm 22 in	838 ± 15 m/s 2850 ± 50 ft/s	1

BALLISTIC LEVEL

NIJ	EN	UL	GUNS & BULLETS
III	B6	4	
		5	
	B5	7	
		8	
IIIA II IIA I	B4	1	
2			
3			
6			





PAK ARMORING (PVT) LTD.

Plot # 2/2A, Survey-86, Sector 24, Main Korangi Creek Road,
Korangi Industrial Area, Karachi, Pakistan.

PHONE: 0303-9234222 - 0303-9234333

EMAIL: info@pakarmoring.com

